

Minimum Edit Distance

Definition of Minimum Edit
Distance

How similar are two strings?

Spell correction

- The user typed “graffe”

Which is closest?

- graf
- graft
- grail
- giraffe

- Computational Biology

- Align two sequences of nucleotides

```
AGGCTATCACCTGACCTCCAGGCCGATGCCC  
TAGCTATCACGACCGCGGTTCGATTTGCCCGAC
```

- Resulting alignment:

```
-AGGCTATCACCTGACCTCCAGGCCGA--TGCCC---  
TAG-CTATCAC--GACCGC--GGTCGATTTGCCCGAC
```

- Also for Machine Translation, Information Extraction, Speech Recognition

Edit Distance

The minimum edit distance between two strings

Is the minimum number of editing operations

- Insertion
- Deletion
- Substitution

Needed to transform one into the other

Minimum Edit Distance

Two strings and their **alignment**:

I	N	T	E	*	N	T	I	O	N
*	E	X	E	C	U	T	I	O	N

Minimum Edit Distance

I N T E * N T I O N
| | | | | | | | | |
* E X E C U T I O N
d s s i s

If each operation has cost of 1

- Distance between these is 5

If substitutions cost 2 (Levenshtein)

- Distance between them is 8

Alignment in Computational Biology

Given a sequence of bases

```
AGGCTATCACCTGACCTCCAGGCCGATGCCC  
TAGCTATCACGACCGCGGTTCGATTTGCCCGAC
```

An alignment:

```
-AGGCTATCACCTGACCTCCAGGCCGA--TGCCC---  
TAG-CTATCAC--GACCGC--GGTCGATTTGCCCGAC
```

Given two sequences, align each letter to a letter or gap

Other uses of Edit Distance in NLP

Evaluating Machine Translation and speech recognition

R Spokesman confirms senior government adviser was appointed

H Spokesman said the senior adviser was appointed

S

I

D

I


Named Entity Extraction and Entity Coreference

- **IBM Inc.** announced today
- **IBM** profits
- **Stanford Professor Jennifer Eberhardt** announced yesterday
- for **Professor Eberhardt**...

How to find the Min Edit Distance?

Searching for a path (sequence of edits) from the start string to the final string:

- **Initial state:** the word we're transforming
- **Operators:** insert, delete, substitute
- **Goal state:** the word we're trying to get to
- **Path cost:** what we want to minimize: the number of edits



Minimum Edit as Search

But the space of all edit sequences is huge!

- We can't afford to navigate naïvely
- Lots of distinct paths wind up at the same state.
 - We don't have to keep track of all of them
 - Just the shortest path to each of those revisited states.

Defining Min Edit Distance

For two strings

- X of length n
- Y of length m

We define $D(i,j)$

- the edit distance between $X[1..i]$ and $Y[1..j]$
 - i.e., the first i characters of X and the first j characters of Y
- The edit distance between X and Y is thus $D(n,m)$

Minimum Edit Distance

Computing Minimum Edit Distance

Dynamic Programming for Minimum Edit Distance

Dynamic programming: A tabular computation of $D(n,m)$

Solving problems by combining solutions to subproblems.

Bottom-up

- We compute $D(i,j)$ for small i,j
- And compute larger $D(i,j)$ based on previously computed smaller values
- i.e., compute $D(i,j)$ for all i ($0 < i < n$) and j ($0 < j < m$)

Defining Min Edit Distance (Levenshtein)

Initialization

$$D(i, 0) = i$$

$$D(0, j) = j$$

Recurrence Relation:

For each $i = 1..M$

For each $j = 1..N$

$$D(i, j) = \min \begin{cases} D(i-1, j) + 1 \\ D(i, j-1) + 1 \\ D(i-1, j-1) + \begin{cases} 2; & \text{if } X(i) \neq Y(j) \\ 0; & \text{if } X(i) = Y(j) \end{cases} \end{cases}$$

Termination:

$D(N, M)$ is distance


The Edit Distance Table

N	9									
O	8									
I	7									
T	6									
N	5									
E	4									
T	3									
N	2									
I	1									
#	0	1	2	3	4	5	6	7	8	9
	#	E	X	E	C	U	T	I	O	N

The Edit Distance Table

N	9									
O	8									
I	7									
T	6									
N	5									
E	4									
T	3									
N	2									
I	1									
#	0	1	2	3	4	5	6	7	8	9
	#	E	X	E	C	U	T	I	O	N

$D(i,j) = \min \begin{cases} D(i-1,j) + 1 \\ D(i,j-1) + 1 \\ D(i-1,j-1) + \begin{cases} 2; & \text{if } S_1(i) \neq S_2(j) \\ 0; & \text{if } S_1(i) = S_2(j) \end{cases} \end{cases}$



Edit Distance

$$D(i,j) = \min \begin{cases} D(i-1,j) + 1 \\ D(i,j-1) + 1 \\ D(i-1,j-1) + \begin{cases} 2; & \text{if } S_1(i) \neq S_2(j) \\ 0; & \text{if } S_1(i) = S_2(j) \end{cases} \end{cases}$$

N	9									
O	8									
I	7									
T	6									
N	5									
E	4									
T	3									
N	2									
I	1									
#	0	1	2	3	4	5	6	7	8	9
	#	E	X	E	C	U	T	I	O	N

The Edit Distance Table

N	9	8	9	10	11	12	11	10	9	8
O	8	7	8	9	10	11	10	9	8	9
I	7	6	7	8	9	10	9	8	9	10
T	6	5	6	7	8	9	8	9	10	11
N	5	4	5	6	7	8	9	10	11	10
E	4	3	4	5	6	7	8	9	10	9
T	3	4	5	6	7	8	7	8	9	8
N	2	3	4	5	6	7	8	7	8	7
I	1	2	3	4	5	6	7	6	7	8
#	0	1	2	3	4	5	6	7	8	9
	#	E	X	E	C	U	T	I	O	N

Minimum Edit Distance

Backtrace for Computing Alignments

Computing alignments

Edit distance isn't sufficient

- We often need to **align** each character of the two strings to each other

We do this by keeping a “backtrace”

Every time we enter a cell, remember where we came from

When we reach the end,

- Trace back the path from the upper right corner to read off the alignment

Edit Distance

$$D(i,j) = \min \begin{cases} D(i-1,j) + 1 \\ D(i,j-1) + 1 \\ D(i-1,j-1) + \begin{cases} 2; & \text{if } S_1(i) \neq S_2(j) \\ 0; & \text{if } S_1(i) = S_2(j) \end{cases} \end{cases}$$

N	9									
O	8									
I	7									
T	6									
N	5									
E	4									
T	3									
N	2									
I	1									
#	0	1	2	3	4	5	6	7	8	9
	#	E	X	E	C	U	T	I	O	N

MinEdit with Backtrace

n	9	↓ 8	↙←↓ 9	↙←↓ 10	↙←↓ 11	↙←↓ 12	↓ 11	↓ 10	↓ 9	↙ 8	
o	8	↓ 7	↙←↓ 8	↙←↓ 9	↙←↓ 10	↙←↓ 11	↓ 10	↓ 9	↙ 8	← 9	
i	7	↓ 6	↙←↓ 7	↙←↓ 8	↙←↓ 9	↙←↓ 10	↓ 9	↙ 8	← 9	← 10	
t	6	↓ 5	↙←↓ 6	↙←↓ 7	↙←↓ 8	↙←↓ 9	↙ 8	← 9	← 10	←↓ 11	
n	5	↓ 4	↙←↓ 5	↙←↓ 6	↙←↓ 7	↙←↓ 8	↙←↓ 9	↙←↓ 10	↙←↓ 11	↙↓ 10	
e	4	↙ 3	← 4	↙← 5	← 6	← 7	←↓ 8	↙←↓ 9	↙←↓ 10	↓ 9	
t	3	↙←↓ 4	↙←↓ 5	↙←↓ 6	↙←↓ 7	↙←↓ 8	↙ 7	←↓ 8	↙←↓ 9	↓ 8	
n	2	↙←↓ 3	↙←↓ 4	↙←↓ 5	↙←↓ 6	↙←↓ 7	↙←↓ 8	↓ 7	↙←↓ 8	↙ 7	
i	1	↙←↓ 2	↙←↓ 3	↙←↓ 4	↙←↓ 5	↙←↓ 6	↙←↓ 7	↙ 6	← 7	← 8	
#	0	1	2	3	4	5	6	7	8	9	
	#	e	x	e	c	u	t	i	o	n	

Adding Backtrace to Minimum Edit Distance

Base conditions:

$$D(i, 0) = i$$

$$D(0, j) = j$$

Termination:

$$D(N, M) \text{ is distance}$$

Recurrence Relation:


For each $i = 1 \dots M$

For each $j = 1 \dots N$

$$D(i, j) = \min \begin{cases} D(i-1, j) + 1 & \text{deletion} \\ D(i, j-1) + 1 & \text{insertion} \\ D(i-1, j-1) + \begin{cases} 2; & \text{if } X(i) \neq Y(j) \\ 0; & \text{if } X(i) = Y(j) \end{cases} & \text{substitution} \end{cases}$$

$$\text{ptr}(i, j) = \begin{cases} \text{LEFT} & \text{insertion} \\ \text{DOWN} & \text{deletion} \\ \text{DIAG} & \text{substitution} \end{cases}$$

The Distance Matrix



Every non-decreasing path

from $(0,0)$ to (M, N)

corresponds to
an alignment
of the two sequences

An optimal alignment is composed
of optimal subalignments

Result of Backtrace

Two strings and their **alignment**:

I	N	T	E	*	N	T	I	O	N
*	E	X	E	C	U	T	I	O	N

Performance

Time:

$$O(nm)$$

Space:

$$O(nm)$$

Backtrace

$$O(n+m)$$

Minimum
Edit
Distance

Weighted Minimum Edit
Distance

Weighted Edit Distance

Why would we add weights to the computation?

- Spell Correction: some letters are more likely to be mistyped than others
- Biology: certain kinds of deletions or insertions are more likely than others

Confusion matrix for spelling errors

sub[X, Y] = Substitution of X (incorrect) for Y (correct)

X	Y (correct)																									
	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
a	0	0	7	1	342	0	0	2	118	0	1	0	0	3	76	0	0	1	35	9	9	0	1	0	5	0
b	0	0	9	9	2	2	3	1	0	0	0	5	11	5	0	10	0	0	2	1	0	0	8	0	0	0
c	6	5	0	16	0	9	5	0	0	0	1	0	7	9	1	10	2	5	39	40	1	3	7	1	1	0
d	1	10	13	0	12	0	5	5	0	0	2	3	7	3	0	1	0	43	30	22	0	0	4	0	2	0
e	388	0	3	11	0	2	2	0	89	0	0	3	0	5	93	0	0	14	12	6	15	0	1	0	18	0
f	0	15	0	3	1	0	5	2	0	0	0	3	4	1	0	0	0	6	4	12	0	0	2	0	0	0
g	4	1	11	11	9	2	0	0	0	1	1	3	0	0	2	1	3	5	13	21	0	0	1	0	3	0
h	1	8	0	3	0	0	0	0	0	0	2	0	12	14	2	3	0	3	1	11	0	0	2	0	0	0
i	103	0	0	0	146	0	1	0	0	0	0	6	0	0	49	0	0	0	2	1	47	0	2	1	15	0
j	0	1	1	9	0	0	1	0	0	0	0	2	1	0	0	0	0	0	5	0	0	0	0	0	0	0
k	1	2	8	4	1	1	2	5	0	0	0	0	5	0	2	0	0	0	6	0	0	0	4	0	0	3
l	2	10	1	4	0	4	5	6	13	0	1	0	0	14	2	5	0	11	10	2	0	0	0	0	0	0
m	1	3	7	8	0	2	0	6	0	0	4	4	0	180	0	6	0	0	9	15	13	3	2	2	3	0
n	2	7	6	5	3	0	1	19	1	0	4	35	78	0	0	7	0	28	5	7	0	0	1	2	0	2
o	91	1	1	3	116	0	0	0	25	0	2	0	0	0	0	14	0	2	4	14	39	0	0	0	18	0
p	0	11	1	2	0	6	5	0	2	9	0	2	7	6	15	0	0	1	3	6	0	4	1	0	0	0
q	0	0	1	0	0	0	27	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
r	0	14	0	30	12	2	2	8	2	0	5	8	4	20	1	14	0	0	12	22	4	0	0	1	0	0
s	11	8	27	33	35	4	0	1	0	1	0	27	0	6	1	7	0	14	0	15	0	0	5	3	20	1
t	3	4	9	42	7	5	19	5	0	1	0	14	9	5	5	6	0	11	37	0	0	2	19	0	7	6
u	20	0	0	0	44	0	0	0	64	0	0	0	0	2	43	0	0	4	0	0	0	0	2	0	8	0
v	0	0	7	0	0	3	0	0	0	0	0	1	0	0	1	0	0	0	8	3	0	0	0	0	0	0
w	2	2	1	0	1	0	0	2	0	0	1	0	0	0	0	7	0	6	3	3	1	0	0	0	0	0
x	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	9	0	0	0	0	0	0	0
y	0	0	2	0	15	0	1	7	15	0	0	0	2	0	6	1	0	7	36	8	5	0	0	1	0	0
z	0	0	0	7	0	0	0	0	0	0	0	7	5	0	0	0	0	2	21	3	0	0	0	0	3	0



Weighted Min Edit Distance

Initialization:

$$D(0, 0) = 0$$

$$D(i, 0) = D(i-1, 0) + \text{del}[x(i)]; \quad 1 < i \leq N$$

$$D(0, j) = D(0, j-1) + \text{ins}[y(j)]; \quad 1 < j \leq M$$

Recurrence Relation:

$$D(i, j) = \min \left\{ \begin{array}{l} D(i-1, j) + \text{del}[x(i)] \\ D(i, j-1) + \text{ins}[y(j)] \\ D(i-1, j-1) + \text{sub}[x(i), y(j)] \end{array} \right.$$

Termination:

$D(N, M)$ is distance

Where did the name, dynamic programming, come from?

...The 1950s were not good years for mathematical research. [the] Secretary of Defense ...had a pathological fear and hatred of the word, research...

I decided therefore to use the word, “**programming**”.

I wanted to get across the idea that this was dynamic, this was multistage... I thought, let's ... take a word that has an absolutely precise meaning, namely **dynamic**... it's impossible to use the word, **dynamic**, in a pejorative sense. Try thinking of some combination that will possibly give it a pejorative meaning. It's impossible.

Thus, I thought dynamic programming was a good name. It was something not even a Congressman could object to.”

Richard Bellman, “Eye of the Hurricane: an autobiography” 1984.